

## Rowing tubes - Main dimension

Machine	Model	L	C Bottom bore	A Outside diameter	ABS	PP	PP+GF
Electro Jet		440	∅ 39.8	∅ 48			
Grossenheimer		450	∅ 40.3	∅ 48			
Howa	RMD16/RME	452	∅ 37.2	∅ 45			
Marzoli	BCX16 FT1/FTSDN/FT-6	446	∅ 42	∅ 53.5			
Marzoli	FT6D/FT7D	446	∅ 42	∅ 48		<b>NEW</b>	
NSC	BM 12-13-+4	395	∅ 40.2	∅ 60			
NSC	BM 20	450	∅ 35	∅ 48			
Rieter	F5 F10 F11 F30 F33	446	∅ 42	∅ 53.5			
Rieter		398	∅ 40.3	∅ 47.5			
S. Andrea		425	∅ 40	∅ 60			
Toyoda	FL16 / FL 100	445	∅ 39.35	∅ 46			
Toyoda	FL16 / FL 100 top drim	452	∅ 39.35	∅ 46			
Toyoda	FL16 / FL 100 autodoffing	452	∅ 39.35	∅ 46			
Zinser	RO-WE-MAT	450	∅ 50.3	∅ 56			
ZInser	FL.660 16"	450	∅ 40.3	∅ 48			
Laksmi		450	∅ 40.3	∅ 48			

